The Dye Sensitized Solar Cell

Behind the Scenes of "Sunny Memories" swissnex San Francisco 21 April 2010

Brian E. Hardin Stanford University

Filling in for:

Kevin Sivula Ecole Polytechnique Fédérale de Lausanne (EPFL)




Ecole Polytechnique Fédérale de Lausanne (EPFL)

- EPFL is one of the premier Science and Engineering Universities in Europe
- 6,000 Students
- Over 100 Nationalities with 50% of the teachers coming form outside of Switzerland.
- Michael Grätzel is the most highly cited solar scientist in the world.



Grätzel lab is a five minute walk from Lac Léman and beach volleyball courts.


Dye-Sensitized Solar Cells are Photovoltaic Devices



Power from Solar Cell: $P_{PV} = I_{mp} \times V_{mp}$ Power Conversion Efficiency: $\eta_{PV} = \frac{P_{PV}}{P_{sun}}$ On a sunny day, the power from the sun (P_{sun}) is one kilowatt per meter squared (1 kW/m²).

A new in paradigm in solar energy conversion

The Dye Sensitized solar cell: Low to medium purity materials Low cost processing High Efficiency High Stability




Dye-Sensitized Solar Cell Components

Sensitizing Dye

Titania Nanoparticles


















Chemical Structure of N3 Dye


20 nm Titania nanoparticles


Iodide/Tri-iodide Redox Couple


Dye-Sensitized Solar Cell Schematic




Current Generation in DSCs











Current Generation in DSCs

- 1. Light absorption
- Injection to semiconductor
- 3. Percolation



Current Generation in DSCs

- 1. Light absorption
- 2. Injection to semiconductor
- 3. Percolation
- 4. Regeneration of oxidized dye




- 1. Light absorption
- 2. Injection to semiconductor
- 3. Percolation
- 4. Regeneration of oxidized dye
- 5. Regeneration of oxidized species

Electron energy (eV vs. NHE) TiO₂ Electrolyte Cathode Dye -1.0 **S*** -0.5 Maximum 0 Voltage Red-Ox 0.5e 1.0S°/S⁺ Wide band-gap semiconductor h+ External circuit LOAD

Maximum Voltage in DSCs

The voltage is determined mainly by the titania and redox couple in the electrolyte.

Why Dye-Sensitized Solar Cells are nicknamed the "Grätzel Cell"




O'Regan and M. Gratzel, Nature 1991

Dye-Sensitized Solar Cells are 12% Efficient. What can we do to make them better?

- Develop dyes to absorb more photons
- Create new electrolytes that provide higher voltages.
- Develop Dye-Sensitized Solar Cells that can last for 30 years


Where do we need to absorb the light?


Solar Spectrum



Dye-sensitized solar cells absorb >85% of visible light, but almost no light in the near-infrared.










Various colors in a series-connected dye solar cell module courtesy Dr. Andreas Hinsch, FHI, ISE Freiburg Germany.



Leaf-shaped transparent DSC with four colors courtesy AISIN SEIKI CO., LTD.

Design dyes that broadly absorb light



N749 tri(cyanato)-2.22-terpyridyl-4,44-tricarboxylate)Ru(II)

M.K. Nazeeruddin et al., J. Am. Chem.Soc. 123, 1613, (2001)


Design Near-Infrared Absorbing Dyes

- Can increase power conversion efficiency from 12% to 14% by absorbing light out to 900 nm.
- Probably can't make DSCs >14% using liquid electrolytes.



Stanford/EPFL collaboration through the Center for Advanced Molecular Photovoltaics (CAMP)

Increase the maximum voltage using plastic hole Electron energy conductors (eV vs. NHE)



Potential to make >20% efficient devices by replacing liquid electrolyte with plastic "solidstate" hole conductors.

Current "solid-state" DSCs are only 6.5% efficient.

Very promising research area.

Bach & Grätzel, Nature 1999

Aesthetic Advantages of Grätzel Cells versus conventional Solar Devices


- Dyes determine the color of the device.
- Can be transparent
- Can be flexible
- Easy to make





Solar Powered Solar Panel Sun Glasses

The SIG, or "Self-Energy Converting Sunglasses" are quite simple. The lenses of the glasses have **dye solar cells,** collecting energy and making it able to power your small devices through the power jack at the back of the frame. "Infinite Energy: SIG"



Real Outdoor Test of DSC Modules

Module Unit



Series connected 64 DSC cells Outdoor Test




Kariya City at lat. 35°10'N, Asimuthal angle: 0° Facing due south, Tilted at 30°




High School Students make their own solar cell





anthocyanine dye from blackberries





Acknowledgement Present LPI Members (Director: Prof. Michael Graetzel)

PhD Students: Jan Cornelius Brauer, Jérémie Brillet, Aravind Kumar Chandiran, Maurin Cornuz, Leo-Philipp Heiniger, Florian Le Formal, Magdalena Marszalek, Rebecca Mitchell, Soo-Jin Moon, Adriana Paracchino, Nuttapol Pootrakulchote, Joël Teuscher, Sophie Wenger

Postdocs: Etienne Baranoff, Takeru Bessho, Lioz Etgar, Il Jung, Andreas Kay, Céline Marie Leroy, Thomas Moehl, Angela Punzi, Ines Raabe, Frédéric Sauvage, Nail Malikovich Shavaleev, Kevin Sivula, Elijah Thimsen, Nicolas Tétreault, Mingkui Wang, Scott Warren, Jun-Ho Yum

Staff Scienctists: Ngoc-Le Cevey-Ha, Carole Graetzel, Robin Humphry-Baker, Kuppuswamy Kalyanasundaram, Paul Liska, Jacques-E. Moser (titled professor), Md. Khaja Nazeeruddin, Peter Pechy, Guido Rothenberger, François Rotzinger, Shaik M. Zakeeruddin


Technical and administrative staff: Pascal Comte, Francine Duriaux Arendse, Jean-David Décoppet, Ursula Gonthier, Nelly Gourdou, Manuel Tschumi

Guest Scientists: Masataka Katono, Stanley David Tilley

We are grateful for funding from:

Stanford University, KAUST Center for Advanced **Molecular Photovoltaics (CAMP),** Swiss CTI, CCEM-CH **Swiss National Science Foundation, Swiss Energy Office US Air Force (European Office of Aerospace Research and Development**) FP7 European Joule Projects: DSC-ROBUST *, NANOPEC, INNOVASOL European Research Council, Adv. Res. Grant. **GRL Korea (with KRICT) Industrial Partners**,

* DSC-Robust project coordinated by ECN Patten , This proposal received highest rating (15/15) of all proposals in energy field during first EU-FP7 call.



ight absorption and charge transport are **decoupled**

elaxed constraints on individual components (each can be separately tuned)

harge carriers (excited electrons) are produced throughout the semiconductor

emiconductor considerations:

- Precise doping
- high purity
- high crystalinity

Solar Cell Efficiencies







Silicon Solar Cell Efficiencies:

Theoretical Maximum: 26%

Best in Lab: 25% (Green, UNSW)

Modules: 15-22%

Thin Film Solar Cell Efficiencies:

Theoretical Maximum: >22%

Best in Lab: 20% (Noufi, NREL)

Modules: 9-12%

Dye-Sensitized Solar Cell Efficiencies:

Theoretical Maximum: 14-20%

Best in Lab: 12% (Grätzel, EPFL)

Modules: 6-9%