Greenhouse Type Based on Utility

PROTECTED CULTIVATION AND POST HARVEST TECHNOLOGY (ASAE3204)

- Classification can be made depending on the functions or utilities.
- ➢ Of the different utilities, artificial cooling and heating are more expensive and elaborate.
- \succ Hence based on this, they are classified in to two types.
 - 1. Greenhouses for active heating.
 - 2. Greenhouses for active cooling.

Greenhouses for active heating

- During the night time, air temperature inside greenhouse decreases.
- The requirements for heating greenhouse depend on the rate at which the heat is lost to the outside environment.
- Various methods are adopted to reduce the heat losses, viz., using
- 1. Double layer polyethylene,
- 2. Thermo pane glasses (two layers of factory sealed glass with dead air space) or
- 3. Heating systems, such as unit heaters, central heat, radiant heat and solar heating system.



Greenhouses for active cooling

- During summer season, it is desirable to reduce the temperatures of greenhouse than the ambient temperatures, for effective crop growth.
- This type of greenhouse either consists of evaporative cooling pad with fan or fog cooling .
- This greenhouse is designed in such a way that it permits a roof opening of 40%-100%.



Greenhouse Type Based on Construction

- The type of construction is influenced by structural material, though the covering material also influences the type.
- → Higher the span, stronger should be the material.
- ➢ So based on construction, greenhouses can be classified as:
- 1. Wooden framed structure.
- 2. Pipe framed structure.
- 3. Truss framed structure.

Wooden framed structures

- The span of green house is less than 6 m.
- Side posts and columns are constructed of wood without the use of a truss.
- Pine wood is commonly used as it is inexpensive and possesses the required strength.
- Timber locally available, with good strength, durability and machinability also can be used for the construction.

Wooden framed structures



Pipe framed structures

- Pipes are used for construction of greenhouses, when the clear span is around 5-12m.
- In general, the side posts, columns, cross ties and purlins are constructed using pipes. In this type, the trusses are not used.

Pipe framed structures



Truss framed structures

- If the greenhouse span is greater than or equal to 15m, truss frames are used.
- Flat steel, tubular steel or angular iron is welded together to form a truss encompassing rafters, chords and struts.
- Struts are support members under compression and chords are support members under tension.

- Angle iron purlins running throughout the length of greenhouse are bolted to each truss.
- Columns are used only in very wide truss frame houses of 21.3 m or more.
- Most of the glass houses are of truss frame type, as these frames are best suited for pre-fabrication.

Truss framed structures



Greenhouse type based on covering materials

Covering materials are the major and important component of the greenhouse structure.

- Covering materials have direct influence on the greenhouse effect inside the structure and they alter the air temperature inside the house.
- The types of frames and method of fixing also varies with the covering material.
- ➢ Based on the type of covering materials, the greenhouses are classified as:
- 1. Glass,
- 2. Plastic Film And
- 3. Rigid Panel Greenhouses.

Glass greenhouses

- Glass as covering material has the advantage of greater interior light intensity.
- These greenhouses have higher air infiltration rate which leads to lower interior humidity and better disease prevention.
- Lean-to type, even span, ridge and furrow type of designs are used for construction of glass greenhouse.

Glass greenhouses



Plastic film greenhouses

- Flexible plastic films including *polyethylene*, *polyester and polyvinyl chloride* are used as covering material in this type of greenhouses.
- Plastics as covering material for greenhouses have become popular, as they are cheap and the cost of heating is less when compared to glass greenhouses.
- The main *disadvantage* with plastic films is its *short life*.

- For example, the best quality ultraviolet (UV) stabilized film can last for 4 years only.
- Polycarbonate has a life span of 15-20 years.
- Polycarbonate is better than glass.
- Quonset design as well as gutter-connected design is suitable for using this covering material.



Rigid panel greenhouses

- Polyvinyl chloride rigid panels, fibre glassreinforced plastic, acrylic and polycarbonate rigid panels are employed as the covering material.
- This material is more resistant to breakage and the light intensity is uniform throughout the greenhouse when compared to glass or plastic.
- High grade panels have long life even up to 20 years.
- The main disadvantage is that these panels tend to *collect dust* as well as to harbor algae, which results in darkening of the panels and subsequent reduction in the light transmission



Polycarbonate Covering



Greenhouse type based on cost of construction

- 1. High cost Green House
- 2. Medium cost Green House
- 3. Low cost Green House

Low cost greenhouse

- These are of simple structure constructed with locally available materials such as bamboo, timber etc.
- \succ The ultra violet (UV) film is used as cladding materials.
- No specific control device for regulating environmental parameters inside the greenhouse are provided.
- Simple techniques are, however, adopted for increasing or decreasing the temperature and humidity.
- Even light intensity can be reduced by incorporating shading materials like nets.

- The temperature can be reduced during summer by opening the side walls.
- Such structure is used as rain shelter for crop cultivation.
- Otherwise, inside temperature is increased when all sidewalls are covered with plastic film.
- This type of greenhouse is mainly suitable for cold climatic zone.



Medium cost greenhouse

- Greenhouse users prefers to have manually or semiautomatic control arrangement owing to minimum investment.
- This type of greenhouse is constructed using galvanized iron (G.I) pipes.
- The canopy cover is attached with structure with the help of screws.
- ➤ Whole structure is firmly fixed with the ground to withstand the disturbance against wind.
- Exhaust fans with thermostat are provided to control the temperature.

- Evaporative cooling pads and misting arrangements are also made to maintain a favorable humidity inside the greenhouse.
- As these system are semi-automatic, hence, require a lot of attention and care, and it is very difficult and cumbersome to maintain uniform environment throughout the cropping period.
- These greenhouses are suitable for dry and composite climatic zones.

High cost greenhouse

- To overcome some of the difficulties in medium-tech greenhouse, a hi-tech greenhouse where the entire device, controlling the environment parameters, are supported to function automatically.
- There is a control system consisting of sensor, computers and data logger (signal receiver).
- All the control systems are aim to provide satisfying the condition provided by the sensor.
- The whole system is controlled by the help of microprocessor and operator.



Shading net



- Shade nettings are designed to protect the crops and plants from UV radiation, and provide protection from climate conditions.
- Better growth conditions can be achieved for the crop due to the controlled micro-climate conditions "created" in the covered area, with shade netting, which results in higher crop yields.

- All nettings are UV stabilized to fulfill expected lifetime at the area of exposure.
- They are characterized of high tear resistance, low weight for easy and quick installation with a 30-90% shade value range.
- ➤ A wide range of shading nets are available in the market which are defined on the basis of the percentage of shade they deliver to the plant growing under them.



