Mechanism of solid mixing, liquids mixing and semisolids mixing

Shubhashree Das Assistant Professor School of Pharmacy and Life Sciences Centurion University of Technology and Management Bhubaneswar shubhashree.das@cutm.ac.in

Classification of mixing

- A. Mixing of solids
- B. Mixing of liquids
- C. Mixing of immiscible liquids
- D. Mixing of semisolids



A. Mixing of solids

- In the manufacture of tablets or granules normally a number of additives are added. Therefore mixing of powder becomes essential part of the process.
- Mixing is considered as a critical factor, especially in case of potent drugs and low dose drugs where high amounts of adjuvants are added.
- The diverse characteristics of particles such as size shape volume surface area density porosity flow charge contribute to the solid mixing.
- Depending on their flow properties solids are divided into two classes as cohesive and non cohesive.

Mechanism of mixing of solids

1. Convective mixing/Macro mixing:

Inversion of the powder bed using blades or paddles or screw element, in which large mass of material moves from one place to another.

2. Shear mixing:

In this type, forces of attraction are broken down so that each particle moves on its own between regions of different components and parallel to their surface.

3. Diffusive mixing/Micro mixing:

Involves the random motion of particle within the powder bed, thereby particles change their position relative to one another.

Classification of equipment for solid mixing

• Based on **flow properties**:

1.Free flowing solids:

e.g.: V cone blend , Double cone blender 2.Cohesive solids:

e.g.: Sigma blender, Planetary mixer

• Based on scale of mixing:

1.Batch type(small scale):

e.g.: Mortar and pestle, V cone blender, Double cone blender, Ribbon blender, Sigma blender, Planetary paddle, Fluidized mixer

2.Continuous type(large scale):

e.g.: barrel type, zigzag type

B. Mixing of Fluids

Mechanism:

- Bulk transport: Movement of large portion o a material from one location to another location in a give system. Rotating blades and paddles are used.
- Turbulent mixing: Highly effective, mixing is due to turbulent flow which results in random fluctuation of the fluid velocity at any given point within the system. Fluid velocity at a given point changes in 3 directions (X, Y and Z).
- Laminar mixing: Mixing of two dissimilar liquids through laminar flow, i.e., applied shear stretches the interface between them. Suitable for liquids which require moderate mixing.
- Molecular diffusion: Mixing at molecular level in which molecules diffuse due to thermal motion.

Mixing Apparatus for fluids

- A Container and
- A Mixing Device or Impeller



Mixing Device

Based on shape and pitch , the are classified into 3 types,

»Propellers
»Turbines
»Paddles

D. Mixing of semisolids

- Semi solids dosageforms include ointments, pastes, creams, jellies, etc., while mixing such dosageforms, the material must be brought to the agitator or the agitator must move the material throughout the mixer.
- The mixing action include combination of low speed shear, smearing, wiping, folding, stretching and compressing.
- A large amount of mechanical energy is applied to the material by moving parts. Sometimes a part of the supplied energy appears as heat.
- The forces required for efficient mixing are high and consumption of power is also high. Hence the equipment must be rugged constructed to tolerate these forces.
- Some semisolids exhibit dilatant property i.e., viscosity increases with increase in shear rates. Therefore, mixing must be done at lower speeds.
- The speed must be changed accordingly to thixotropic, plastic and pseudo plastic materials.

Classification of equipment

• Agitator mixers:

e.g.:- Sigma mixers and Planetary mixer.

• Shear mixers:

e.g.:- Triple roller mill and Colloidal mill.

Selection of mixing equipment for semi solids

- Physical properties of the materials density viscosity and miscibility.
- Economic considerations regarding processing time required for mixing and power consumption.
- The cost of equipment and its maintenance.

