

# MSCS2104-PENETRATION TESTING & VULNERABILITY ASSESSMENT

## MODULE (I)

### Session 1



### What is OWASP?

The Open Web Application Security Project, or OWASP, is an international non-profit organization dedicated to web application security. One of OWASP's core principles is that all of their materials be freely available and easily accessible on their website, making it possible for anyone to improve their own web application security. The materials they offer include documentation, tools, videos, and forums. Perhaps their best-known project is the OWASP Top 10.

### What is the OWASP Top 10?

The OWASP Top 10 is a regularly-updated report outlining security concerns for web application security, focusing on the 10 most critical risks. The report is put together by a team of security experts from all over the world. OWASP refers to the Top 10 as an 'awareness document' and they recommend that all companies incorporate the report into their processes in order to minimize and/or mitigate security risks.

### Introduction to web applications security

In the process of building a Web application, security measures are not often taken into account by the web developers, especially if you're working with security experts—we tend to let them deal with the global aspect of security which is not always ideal.

The Open Web Application Security Project (OWASP) is an online community that produces freely-available articles, documentation, tools, or security advises for web applications. The list we're about to cover does not enumerate all the problems related to web application security but instead, outlines the top 10 based on what security experts see while performing penetration testing.

The OWASP Top 10 is a standard awareness document for developers and web application security. It represents a broad consensus about the most critical security risks to web applications.

### Top 10 Web Application Security Risks

1. **Injection**. Injection flaws, such as SQL, NoSQL, OS, and LDAP injection, occur when untrusted data is sent to an interpreter as part of a command or query. The attacker's hostile data can trick the interpreter into executing unintended commands or accessing data without proper authorization.
2. **Broken Authentication**. Application functions related to authentication and session management are often implemented incorrectly, allowing attackers to compromise

passwords, keys, or session tokens, or to exploit other implementation flaws to assume other users' identities temporarily or permanently.

3. **Sensitive Data Exposure**. Many web applications and APIs do not properly protect sensitive data, such as financial, healthcare, and PII. Attackers may steal or modify such weakly protected data to conduct credit card fraud, identity theft, or other crimes. Sensitive data may be compromised without extra protection, such as encryption at rest or in transit, and requires special precautions when exchanged with the browser.
4. **XML External Entities (XXE)**. Many older or poorly configured XML processors evaluate external entity references within XML documents. External entities can be used to disclose internal files using the file URI handler, internal file shares, internal port scanning, remote code execution, and denial of service attacks.
5. **Broken Access Control**. Restrictions on what authenticated users are allowed to do are often not properly enforced. Attackers can exploit these flaws to access unauthorized functionality and/or data, such as access other users' accounts, view sensitive files, modify other users' data, change access rights, etc.
6. **Security Misconfiguration**. Security misconfiguration is the most commonly seen issue. This is commonly a result of insecure default configurations, incomplete or ad hoc configurations, open cloud storage, misconfigured HTTP headers, and verbose error messages containing sensitive information. Not only must all operating systems, frameworks, libraries, and applications be securely configured, but they must be patched/upgraded in a timely fashion.
7. **Cross-Site Scripting XSS**. XSS flaws occur whenever an application includes untrusted data in a new web page without proper validation or escaping, or updates an existing web page with user-supplied data using a browser API that can create HTML or JavaScript. XSS allows attackers to execute scripts in the victim's browser which can hijack user sessions, deface web sites, or redirect the user to malicious sites.
8. **Insecure Deserialization**. Insecure deserialization often leads to remote code execution. Even if deserialization flaws do not result in remote code execution, they can be used to perform attacks, including replay attacks, injection attacks, and privilege escalation attacks.
9. **Using Components with Known Vulnerabilities**. Components, such as libraries, frameworks, and other software modules, run with the same privileges as the application. If a vulnerable component is exploited, such an attack can facilitate serious data loss or server takeover. Applications and APIs using components with known vulnerabilities may undermine application defenses and enable various attacks and impacts.
10. **Insufficient Logging & Monitoring**. Insufficient logging and monitoring, coupled with missing or ineffective integration with incident response, allows attackers to further attack systems, maintain persistence, pivot to more systems, and tamper, extract, or destroy data. Most breach studies show time to detect a breach is over 200 days, typically detected by external parties rather than internal processes or monitoring.