

PRESENTATION ON

INTIATION TECHNIQUES AND INITIATING DEVICES

CUFS 2416 EXPLOSIVE AND POST BLAST INVESTIGATION

B.SC. FORENSIC SCIENCE (SEM 6) SCHOOL OF FORENSIC SCIENCES BHUBANESHWAR CAMPUS


CONTENT

- Introduction
 - Explosive train
 - Low explosive train
 - High explosive train
 - Dynamites
 - Detonators
 - Safety fuse
- Applications

EXPLOSIVE TRAIN

- An explosive train is also called as firing train.
- An explosive train is a sequence of events which begins with relatively low level of energy that causes a chain reaction to initiate the final explosive or main charge.
- It is divided into two types

 - 1. Low explosive train. 2. High explosive train



LOW EXPLOSIVE TRAIN


- For example:- Rifle cartridge which consists of
- A primer consisting of a small amount of primary high explosive which initiates the explosive train.
- An igniter which is initiated by the primer and creates a flame that ignites the propellant.
- As the propellant consisting of a secondary low explosive that emits a large amount of gas as it deflagrates.

HIGH EXPLOSIVE TRAIN

- High explosive train are two types
- 1. Detonators 2. Dynamites

Detonators


- Detonators containing primary explosive.
- Primary explosives require small quantity of energy to initiate.
- These are extremely sensitive to heat, shock, and friction.
- Eg:- Lead Azide, mercury fulminate.



DYNAMITES

- Dynamites containing secondary explosive.
- These are insensitive to shock ,heat, and friction.
- These are less sensitive than primary explosive.

Eg:-PETN,TNT,RDX.



Dynamite contains:-

Primary component: - High explosive train includes 3 primary high explosive components which are used to initiate explosive. (fuse, primer, Detonator).

Secondary components: - Secondary high explosive components contains boosters.

Eg:-TNT,PETN,HMX etc.

Tertiary components:- These are main charges . Eg :- TNT, PETN, HMX

• As main charge is insensitive sometime so explosive boosters is used to deliver a sufficient shock wave to initiate the main charge as so full detonation occurs.

Eg:-ANFO

DETONATORS

- A Detonator is a device used to trigger an explosive device.
- It may be in different ways such as impact, friction, electricity, heat etc.
- Detonator is the transmission through an explosive substance at the speed of 3000 to 9000 meters per second.
- Detonators containing primary explosive. They require small quantity of energy to initiate. They are extremely sensitive to heat, shock and friction.
- Eg :- lead Azide, mercury fulminate.




SAFETY FUSE

- Safety fuse introduction by William Beckford in the year 1831.
- It is a hollow card filled with a mixture resembling black powder and designed to propagate burning at a slow and steady rate.
- Originally it consisted of a tube of gunpowder surrounded by waterproof varnished jute

rope.

• The safety fuse burns at the rate of typically about 30 second per foot.



THANK YOU