Radiation Physics

## Intensifying Screens

- There are three key parts of the Image Receptor for Conventional Radiography:
  - Film to record the image
  - Intensifying Screens to expose the film


- Less than 1% of the incident x-rays interact with the film to contribute to the latent image.
- The intensifying screens converts the remnant radiation to light than produces the latent image. They act as an amplifier of the

- About 30% of the x-rays striking the screens interact with the screens producing a large number of visible light photons.
- The use of intensifying screens results in considerable lower radiation dose to the patient but has the disadvantage of causing a

Most conventional radiographic cassettes have a pair of screens that sandwich the film. This design used double emulsion film.

#### Screen Construction

- Four Distinct Layers
  - Protective Coating
  - Phosphor
  - Reflective layer
  - Base



## **Protective Coating**

- Coating is transparent to light.
- Resistant to abrasion and damage from handling.
- Resistant to static electricity
- Provide a surface for cleaning while protecting the phosphors.

## Phosphors

- The active layer of the screen is the phosphors.
- The phosphors emit light when stimulated by x-rays.
- Prior to 1970 the most common phosphor was a crystalline form of Calcium Tungstate.

# Phosphors

- Modern screens use rare earth elements such as:
  - Gadolinium
  - Lanthanum
  - Yttrium

### Properties of Phosphors used in Intensifying Screens

High atomic number so x-ray absorption will be high. Quantum Detective Efficiency (DQE)

Emit a large amount of light per x-ray absorption. Conversion Efficiency


## Properties of Phosphors used in Intensifying Screens

Phosphor Afterglow should be minimal.

 Phosphor should not be affected by heat humidity or other environmental conditions Influences of the Action of Intensifying Screens

Thickness of the phosphor Layer

Concentration of the crystals



# Reflective Layer

The light from the phosphors is emitted isotropically.

Without a reflective layer, only half of the light would interact with the film.

# Reflective Layer

Some screens have special dyes that absorb the light photons coming at a large angles.


These photons would increase the image blur.

#### Base

> The base is the layer farthest from the film.

- It is usually made of polyester. The base should be:
  - Rugged and moisture resistant
  - Can not be damaged by radiation or discoloration

#### Luminescence



- The x-ray photon is absorbed by the target atom.
- The outer shell electron is raised to an excited state.

#### Luminescence

- Any material that gives of light in response to a stimulus is a luminescent material.
- Two types of luminescent material.
- Fluorescent: gives off light only during stimulus. Good for screens
- Phosphorescence: continues to give off

Phosphor composition: Rare earth screens are very efficient in conversion of x-ray to light.

- Phosphor thickness: The thicker the phosphor layer, the higher the number of xrays converted to light.
- High speed screens have thick layer. Detail screens have a thin layer.
- Reflective layer will increase speed and

Dye: Light controlling dyes are added to control the light spread to improve spatial resolution.

Crystal size: Larger crystal produce more light per interaction. Detail screens have

- Concentration of crystals:
  - The higher the concentration of crystals, the higher the speed.

#### Rare Earth Screens


Rare earth screens have increased speed for two reasons:

 Detective Quantum Efficiency (DQE) or the ability to absorb the photons (High Z number)


# Image Noise

- Conversion Efficiency: High conversion efficiency results in increases image noise.
- Noise (any unwanted information) can be speckled appearance or grainy
  - It occurs with fast screens and use of high kVp.
- The factors that make rare earth screens

- Image detail is the result of *spatial* resolution and contrast resolution.
- Generally the conditions that



When screen phosphors reacts with x-rays a larger area of the film is exposed than what would be exposed by radiation alone.



Direct exposure can resolve 50 lp/mm with a very small focal spot.

▶ High speed screens can resolve 7 lp/mm.

Detail screens can resolve 15 lp/mm

High speed screens have thick layers of crystal and /or large crystals.

High detail screens have a thin layer of small crystals.


#### Screen film Combinations

Screens in pairs and double emulsion film is the standard of the industry. Less than 1% of the image is produced by the x-ray photons.

Each screen contributes relatively evenly in the production of the image.


#### Cassettes

- The cassette is a rigid holder for the film and screens.
- It will contain some form of compression to push the film in close contact with the



#### Cassettes

- The back of the cassette may contain some form of metal that can absorb x-rays that are not absorbed by the screens.
- Sometime with cassettes that do not




# Spectrum Matching

For the screen to work at maximum efficiency, the light absorption characteristics of the film must be matched to the light emitted from the screens.

This is called spectrum matching.

# Spectrum Matching

- Calcium Tungstate emits a broad blue spectrum.
- Rare earth emits a green spectrum.
- The film screens



# **Asymmetric Screens**

Screens in the cassette can be of two types or speeds. Some people use two different speeds in cassette for full spine radiography.

When types of screens are different, they are referred to as Asymmetric screens. One side

#### Care of Screens and Cassettes

High quality radiography requires that the screens be clean and free of artifacts.

Avoid touching the screens with your hands.

Clean the screens with screen cleaner.

#### Care of Screens and Cassettes

Keeping the dark room clean will help reduce dirt or dust getting into the cassette.

Don't stack the cassette on top of each other as the weight can damage the cassette.

#### Care of Screens and Cassettes

Clean the screens at least quarterly

 Use only specially formulated screen cleaner with anti static properties

Never use alcohol to clean screens

# Examples of Screen Problems

The hinge of the cassette has failed, resulting in a light leak.



## Cassette & Screen Problems

Card inside cassette



## Cassette Artifacts

- This cassette popped partly open.
- With cassette artifacts, think about how the



## Cassette Artifacts

- Dirty screens will appear as white spots on the film.
- This film also has some static electricity artifacts.



# Cassette Artifact Dirty Screens

Dirty or damaged screens will cause white spots on the image.




# Dirty or Damaged Screens

Dirty or damaged screen will cause white spots on the image.



# Dirty & Damaged Screens

The white spots on this film are the result of damaged or worn out screens.



- Poor screen contact will cause an area of the image to appear cloudy and blurry.
- Common reasons for poor contact include:
  - Worn contact felt
  - Loose, bent or broken hinges
  - Loose bent or broken latches

- Common reasons for poor contact include:
  - Warped cassette front or frame.
  - Sprung or cracked cassette frame.
  - Foreign matter in the cassette.

Screen contact is tested using a wire mesh

A radiograph is taken and the film processed.

The image is viewed from 2 to 3 meters from the view box.

Poor contact will appear as a cloudy and


Test the cassette when they are purchased and then twice yearly.

# Screen Contact Testing

#### Procedure:

Clean screens and let them dry. Use screen cleaner design for the screen used.


With a felt tip pen, write an identification number



# Screen Contact Testing

#### Procedure:

- Set SID to 40" Table Top
- Place cassette on table.
- Place wire mesh tool on cassette.



## Screen Contact Testing

Procedure:

Hang film on view box.

Step back 72" from view box and view film.



There is a loss of detail in the thoracic and lumbar spine due to poor screen contact.



Note the blurry image in the spine but sharp image of the ribs.

The screens were not in proper contact in

